

# Wire Rope Accessories



## Regular Wire Rope Thimbles

TRADE SIZE (IN)	ITEM NO. BZ	ITEM NO. SST316	LBS. /100 PCS.	PKG. QTY.
1/8"	05202	05202S	3	25
3/16"	05204	05204S	3	25
1/4"	05206	05206S	4	25
5/16"	05207	05207S	6	25
3/8"	05208	05208S	8	25
1/2"	05210	05210S	13	25

Uses: Used with wire rope clips to make a solid eye in cable or rope.

**BZ:** Steel with bright zinc finished

**SST316:** Stainless steel #316

**Warning: Not recommended for overhead lifting.**



## Hvy Wire Rope Thimbles - Hot Galv.

TRADE SIZE (IN)	ITEM NO.	LBS. / 100 PCS.
1/4"	05312	6
5/16"	05313	12
3/8"	05314	25
7/16"	05315	50
1/2"	05316	51
5/8"	05318	75
3/4"	05319	147
7/8"	05020	175
1"	05021	275

Uses: A rugged rope thimble recommended for heavy duty service.

**Warning: Not recommended for overhead lifting.**

## Wire Rope Sleeves(Oval or 8 Shape)

TRADE SIZE (IN)	ITEM NO. *AL.	ITEM NO. **COPPER	LBS. / 100 PCS.	PKG. QTY.
1/16"	05402	05402C	0.10	100
3/32"	05403	05403C	0.16	50
1/8"	05404	05404C	0.29	50
5/32"	05405	05405C	0.45	50
3/16"	05406	05406C	0.45	50
1/4"	05408	05408C	0.79	50
5/16"	05410	05410C	0.92	50
3/8"	05412	05412C	1.34	50
7/16"	05414	05414C	1.68	50
1/2"	05416	05416C	2.10	50

Uses: To make a solid eye in cable.

\*AL: Aluminum

\*\*Copper: zinc coated copper



## Wire Rope Clips

TRADE SIZE (IN)	ITEM NO. BZ	ITEM NO. SS316	LBS. /100 PCS.	PKG. QTY.
1/16"	05001	05001S	2	25
1/8"	05003	05003S	4	25
3/16"	05005	05005S	7	25
1/4"	05007	05007S	14	25
5/16"	05008	05008S	15	25
3/8"	05009	05009S	21	25
1/2"	05011	05011S	37	25
5/8"	05013		59	10
3/4"	05014		84	10

Uses: Most common method of attaching wire rope to equipment.

**BZ:** Steel with bright zinc finished

**SST316:** Stainless steel #316



## Forged Wire Rope Clips - Hot Galv.

TRADE SIZE (IN)	ITEM NO.	LBS. / 100 PCS.
1/4"	05107	18
5/16"	05108	30
3/8"	05109	47
1/2"	05111	76
5/8"	05113	106
3/4"	05114	150
7/8"	05115	212
1"	05116	260

Uses: Stronger than malleable wire rope clips, with a more rust resistant surface finish. Commonly used for attaching wire rope to equipment.

**Warning: 1/8" to 3/8" use at least two clips, 1/2" to 5/8" at least three clips, 3/4" to 7/8" at least four clips, 1" at least five clips for each connection.**

