



# Coil Chain & Utility Chain

## Coil Chain - Straight Link



TRADE SIZE	ITEM NO.	MATERIAL DIAMETER INCHES	INSIDE LENGTH INCHES	INSIDE WIDTH INCHES	WORKING LOAD LIMIT LBS.	POUNDS PER PACKAGE	LENGTH PER PACKAGE FEET	PACKAGE DESCRIPTION
2	10505	0.148	1.18	0.26	310	21	125	REEL
2/0	10507	0.192	1.26	0.34	520	33.5	125	REEL
4/0	10508	0.218	1.39	0.38	670	47	125	REEL
1/0	11038	0.177	1.25	0.31	440	24.5	100	BOX
2/0	11039	0.192	1.26	0.34	520	26.5	100	BOX
4/0	11041	0.218	1.39	0.38	670	35	100	BOX
5/0	11042	0.250	1.52	0.44	880	48	100	BOX
2/0	13515	0.192	1.26	0.34	520	92	350	PAIL
2/0	13715	0.192	1.26	0.34	520	568	2100	DRUM

Uses - Electrically welded chain for light duty, general utility service. Such as in animal ties, platform guard, tailgate and many other uses.

**Finish - Bright Zinc. Other finishes available.**

**Caution: Do not use for overhead lifting. Working load limit must not be exceeded.**

Meet NACM 2010 and ASTM A413-07 Standard.

## Coil Chain - Twist Link



TRADE SIZE	ITEM NO.	MATERIAL DIAMETER INCHES	INSIDE LENGTH INCHES	INSIDE WIDTH INCHES	WORKING LOAD LIMIT LBS.	POUNDS PER PACKAGE	LENGTH PER PACKAGE FEET	PACKAGE DESCRIPTION
1/0	10510	0.177	1.22	0.27	415	20	100	REEL
1/0	13524	0.177	1.22	0.27	415	70	350	PAIL

Uses - "Twisted from coil chain straight link" For light duty, general utility service, such as in animal ties, padlock holding chain and other uses.

**Finish - Bright Zinc.**

**Caution: Do not use for overhead lifting. Working load limit must not be exceeded.**

Meet NACM 2010 and ASTM A413-07 Standard.

## Utility Link Chain



TRADE SIZE	ITEM NO.	MATERIAL DIAMETER INCHES	INSIDE LENGTH INCHES	INSIDE WIDTH INCHES	WORKING LOAD LIMIT LBS.	POUNDS PER PACKAGE	LENGTH PER PACKAGE FEET	PACKAGE DESCRIPTION
0.135	10570	0.135	1.36	0.34	340	13	100	REEL

Uses - A light duty chain for many miscellaneous uses. i.e. Security lock, etc.

**Finish - Bright Zinc.**

**Caution: Do not use for overhead lifting. Working load limit must not be exceeded.**

Meet NACM 2010 and ASTM A413-07 Standard.